



- Motorised dampers
- ABS/polypropylene housing & blades
- Drive open / drive shut
- 240VAC or 24VAC
- Mass 1.0 to 2.8 kg
- Supplied with 600mm of three core lead
- 24VAC models utilize a fusible resistor which will become open circuit within 2 seconds if accidentally connected to 240VAC
- Suitable for horizontal or vertical mounting
- For in-line ducted applications

Stock Code	Metric Size	Imperial Size	Voltage	Frequency	Power	Open/close time	Twin/single blade	Shut-off percentage	Max. airflow	Mass
	mm	inches	VAC	Hz	W	s		%	l/s	kg
806	150	6	240	50	5	60	Twin	98	100	1.0
808	200	8	240	50	5	60	Twin	98	200	1.1
810	250	10	240	50	5	60	Twin	98	300	1.5
812	300	12	240	50	5	60	Single	94	700	2.3
814	350	14	240	50	5	60	Single	94	1200	2.8
826	150	6	24	50	5	60	Twin	98	100	1.0
828	200	8	24	50	5	60	Twin	98	200	1.1
830	250	10	24	50	5	60	Twin	98	300	1.5
832	300	12	24	50	5	60	Single	94	700	2.3
834	350	14	24	50	5	60	Single	94	1200	2.8

Wiring		
Blue	Neutral	
Brown	Active	Open
Black	Active	Close



Paltech Corporation (Aust) Pty Ltd
 Ph: (03) 9894 4444 Fax: (03) 9894 4445
www.paltech.com.au